

# Perlick® SELF-CONTAINED BACK BAR REFRIGERATOR 1-, 2-, 3- AND 4-DOOR



BBS36 with optional glass/w/ stainless steel door shown



BBS36 with optional wine drawers shown



JOB	
AREA	
ITEM NO.	
MODEL NO.	

BBS36	1-Door Model
BBS60	2-Door Model
BBS84	3-Door Model
BBS108	4-Door Model

NSF/ANSI Standard 7 Listed for open food storage.  
Note: Models furnished with wine temperature are listed for the storage and display of bottled and canned products only.

MODEL NUMBERS		BBS36	BBS60	BBS84	BBS108
<b>NUMBER OF COMPARTMENTS</b>		1	2	3	4
<b>EXTERIOR CABINET DIMENSIONS</b>	Length - in. (mm)	36 (914)	60 (1524)	84 (2134)	108 (2743)
	Depth - in. (mm)	24¾ (629)	24¾ (629)	24¾ (629)	24¾ (629)
	Height - in. (mm)	34⅞ (878)	34⅞ (878)	34⅞ (878)	34⅞ (878)
<b>INTERIOR CABINET DIMENSIONS</b>	Length - in. (mm)	20 (508)	44 (1118)	68 (1727)	92 (2337)
	Depth - in. (mm)	18¾ (476)	18¾ (476)	18¾ (476)	18¾ (476)
	Height - in. (mm)	28½ (724)	28½ (724)	28½ (724)	28½ (724)
<b>INTERNAL VOLUME Net. Cu. Ft. (Litres)</b>		7.4 (210)	16 (453)	24.8 (702)	33.5 (949)
<b>PRODUCT CAPACITY</b>	CASE PACK - 12 OZ. BOTTLE/CAN	182/273	371/553	581/868	791/1183
	STAGGERED - 12 OZ. BOTTLE/CAN	196/292	400/592	628/932	856/1272
<b>SHIPPING WEIGHT Lbs. (kg.)</b>		254 (115)	340 (154k)	490 (222)	671 (304)
<b>ELECTRICAL SPECIFICATIONS</b>	<b>Electrical Supply</b>	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph	120 VAC/60 Hz/1 Ph
	<b>Running Load Amps</b>	3.2	5.5	6.3	6.3
	<b>Electrical Connection</b>	Cord connected	Cord connected	Cord connected	Cord connected
	<b>Cord Plug Type</b>	NEMA 5-15	NEMA 5-15	NEMA 5-15	NEMA 5-15
	<b>Cord Length</b>	8'	8'	8'	8'
	<b>Defrost Initiation</b>	Automatic	Automatic	Automatic	Automatic
	<b>Defrost Type</b>	Off cycle	Off cycle	Off cycle	Off cycle
	<b>Thermostat</b>	Digital control	Digital control	Digital control	Digital control
<b>REFRIGERATION SPECIFICATIONS</b>	<b>Lighting Type</b>	LED	LED	LED	LED
	<b>Horsepower</b>	1/5	1/4	1/3	1/3
	<b>Refrigerant</b>	R134a	R134a	R134a	R134a
	<b>Refrigerant Charge oz.</b>	6.5	7.0	7.0	7.0
	<b>Factory Temperature Setting - Refrigerator F (C)</b>	38° (3.3°)	38° (3.3°)	38° (3.3°)	38° (3.3°)
	<b>Temperature Range - Refrigerator F (C)</b>	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)	33°-40° (0.5°-4.5°)
	<b>Factory Temperature Setting - White Wine F (C)</b>	50°-55° (10.0°-13.0°)	50°-55° (10.0°-13.0°)	50°-55° (10.0°-13.0°)	50°-55° (10.0°-13.0°)
	<b>Factory Temperature Setting - Red Wine F (C)</b>	60°-65° (15.5°-18.0°)	60°-65° (15.5°-18.0°)	60°-65° (15.5°-18.0°)	60°-65° (15.5°-18.0°)
	<b>Temperature Range - Wine F (C)</b>	50°-65° (10.0°-18.0°)	50°-65° (10.0°-18.0°)	50°-65° (10.0°-18.0°)	50°-65° (10.0°-18.0°)
	<b>Condensing Unit Location</b>	Left or Right	Left or Right	Left or Right	Left or Right
	<b>Expansion Device</b>	Capillary tube	Capillary tube	Capillary tube	Capillary tube
<b>Pull-Out Condensing Unit</b>	Yes	Yes	Yes	Yes	
<b>Front Vented</b>	Yes	Yes	Yes	Yes	
<b>PLUMBING</b>		Automatically	Automatically	Automatically	Automatically

# Perlick® SELF-CONTAINED BACK BAR REFRIGERATOR 1-, 2-, 3- AND 4-DOOR

Note: Open floor drain not provided on models intended for non-packaged food.

